



Key Specifications/Special Features

- 1、 Environment condition: -5-40 degree Celsius ;
Relative humidity <85% (+30 degree Celsius);
Atmospheric pressure: 70-106KPa ;
- 2、 Pulling-out force: phosphorus bronze and silver plating (20-40 uinch),
pulling-out force not less than 25N ;
- 3、 The performance of anti-burn: PBT (UL94V-0) or anti-burn ABS (UL94V-0) ,
Combustibility achieved GB/T 5169.7-1985 standard ;
- 4、 Specification: 10 pairs
- 5、 Type: every specification has connection or disconnection types
- 6、 Life: durability 200 cycles
- 7、 Suitable diameter: 0.4-0.6mm(metal).

				10 Pairs orbit clamp module				XL-011B(013B)	
SIGNATURE				DOCUMENT SERIAL NUMBER				SCALE	
DEVISER				NORMALIZER				DRAWING MARK SYMBOL	
PROOFREADER				RATIFIER				QUANTITY	
ASSESSOR				DATE				WEIGHT	
TECHNOLOGIST								SCALE 2:1	
				PAGE NUMBER OF ALL				PAGE HEADER	
								ANSHI Cixi Anshi communication Equipment Co.,Ltd	

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE