



Key Specifications/Special Features

- 1、 Environment condition: -5-40 degree Celsius ;
Relative humidity <85% (+30 degree Celsius);
Atmospheric pressure: 70-106KPa ;
- 2、 Pulling-out force: phosphorus bronze and silver plating (20-40 uinch),
pulling-out force not less than 25N ;
- 3、 The performance of anti-burn: PBT (UL94V-0) or anti-burn ABS (UL94V-0) ,
Combustibility achieved GB/T 5169.7-1985 standard ;
- 4、 Specification: 8 pairs
- 5、 Type: every specification has connection or disconnection types
- 6、 Life: durability 200 cycles
- 7、 Suitable diameter: 0.4-0.6mm(metal).

| | | | | | | | | | | | | |
|-----------|----------|-------------|----------|----------------------|------------|----------|------|---------------------|-------------|--------|-------|--|
| | | | | 8 Pairs clamp module | | | | XL-014-8A/C | | | | |
| SIGNATURE | DESIGNER | PROOFREADER | ASSESSOR | TECHNOLOGIST | NORMALIZER | RATIFIER | DATE | DRAWING MARK SYMBOL | QUANTITY | WEIGHT | SCALE | ANSHI Cixi Anshi communication Equipment Co.,Ltd |
| | | | | | | | | | | | 2:1 | |
| | | | | | | | | PAGE NUMBER OF ALL | PAGE HEADER | | | |

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE