



Key Specifications/Special Features

- 1、 Environment condition: -5-40 degree Celsius ;
Relative humidity <85% (+30 degree Celsius);
Atmospheric pressure: 70-106KPa ;
- 2、 Pulling-out force: phosphorus bronze and silver plating (20-40 uinch),
pulling-out force not less than 25N ;
- 3、 The performance of anti-burn: PBT (UL94V-0) or anti-burn ABS (UL94V-0) ,
Combustibility achieved GB/T 5169.7-1985 standard ;
- 4、 Specification: 8 pairs
- 5、 Type: normal open
- 6、 Life: durability 200 cycles
- 7、 Suitable diameter: 0.4-0.6mm(metal).

				8 Pairs clamp module				XL-014-8B			
SIGNATURE	DESIGNER	PROOFREADER	ASSESSOR	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	ANSHI Cixi Anshi communication Equipment Co.,Ltd
										2:1	
							PAGE NUMBER OF ALL	PAGE HEADER			

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE