



**Key Specifications/Special Features**

- 1、 Environment condition: -5-40 degree Celsius ; Relative humidity <85% (+30 degree Celsius); Atmospheric pressure: 70-106KPa ;
- 2、 Pulling-out force: phosphorus bronze and silver plating (20-40 uinch), pulling-out force not less than 25N ;
- 3、 The performance of anti-burn: PBT (UL94V-0) or anti-burn ABS (UL94V-0) , Combustibility achieved GB/T 5169.7-1985 standard ;
- 4、 Specification: 5 pairs
- 5、 Type: normal open
- 6、 Life: durability 200 cycles
- 7、 Suitable diameter: 0.4-0.6mm(metal).

				5 Pairs clamp module				XL-014-5B			
SIGNATURE	DESIGNER	PROOFREADER	ASSESSOR	SIGNATURE	DATE	DRAWING MARK	SYMBOL	QUANTITY	WEIGHT	SCALE	ANSHI Cixi Anshi communication Equipment Co.,Ltd
										2.5:1	
						PAGE NUMBER OF ALL		PAGE HEADER			

ENREGISTER OF BORROW  
 TRACER  
 PROOFREADER  
 SERIAL NUMBER OF OLD BASE MAP  
 SERIAL NUMBER OF BASE MAP  
 SIGNATURE  
 DATE