



1. Environment condition: -5-40 degree Celsius ; Relative humidity <85% (+30 degree Celsius); Atmospheric pressure: 70-106KPa
2. Pulling-out force: tin bronze and silver plating (20-40 uninch), pulling-out force not less than 25N ;
3. The performance of anti-burn: anti-burn ABS (UL94V-0) ; Combustibility achieved GB/T 5169.7-1985 standard ;
4. Insulated resistance: under standard atmospheric pressure , Insulated resistance no less than 1,000M ohm between the two disjunct connections ;
5. Intermediate resistance between the reed terminators: no more than 7m ohm between intermediate reed under the standard examination condition
6. Dielectric strength: according to industry standard
7. Life: durability 200 cycles

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE

SIGNATURE	SIGNATURE	DATE	Indoor distribution box (30 pairs)				
							DEVISER
DATE	DATE	DATE	DRAWING MARK	SYMBOL	QUANTITY	WEIGHT	SCALE
DATE	DATE	DATE	PAGE NUMBER OF ALL	PAGE HEADER			

AS-DB30

ANSHI Cixi Anshi communication Equipment Co., Ltd