



**Key Specifications/Special Features**

- 1、 Size (mm) L x W x H: 10 pairs: 112 x 22 x 42 ; 8 pairs: 95 x 22 x 42 ;
- 2、 Over-voltage barrier property parameter: direct current electric breakdown strength:  $U_{dc}=190$  to  $260V$  ;  
Pulse electric breakdown strength:  $U_{max} \leq 800V$  ;
- 3、 Environment condition: 5-40 degree Celsius ; Relative humidity <85% (+30 degree Celsius) ;  
Atmospheric pressure: 70-106KPa .
- 4、 The performance of anti-burn: PBT or anti-burn ABS (UL94V-0) , Combustibility achieved GB/T 5169.7-1985 standard ; metal: phosphorus bronze and silver plating (20-40 uinch) ;
- 5、 Type: 2-pole and 3-pole, specification: 8 pairs and 10 pairs .

				3(2)-pole Gas tube arrester magazine				XL-015A(B)	
SIGNATURE	DEPARTMENT	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	
DEVISER			NORMALIZER					2:1	
PROOFREADER			RATIFIER						
ASSESSOR									
TECHNOLOGIST			DATE		PAGE NUMBER OF ALL	PAGE HEADER			
<b>ANSHI</b> Cixi Anshi communication Equipment Co.,Ltd									

ENREGISTER  
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER  
OF OLD BASE MAP

SERIAL NUMBER  
OF BASE MAP

SIGNATURE

DATE