



Key Specifications/Special Features

1. Operation temperature: -40 °C to 60 °C , Relative humidity: 85 %(30 °C) , Air pressure: 70-106Kpa.
2. Insertion force: 2 contacts:350g, 4 contacts:500g, 6 contacts:750g, 8 contacts:900g,
3. IDC: phosphor bronze and silver plating (20~50inch), suitable diameter 0.4-0.6mm, durability 200 cycles ;
4. Contact pin: phosphor bronze and gold plating (20~50inch), mating durability not less than 750 cycles ;
5. Anti-burn performance: plastic made from PPO and PC or PBT(UL94V-0), meeting the international standard ;
6. Intermediate resistance: no more than 20m ohm in normal atmosphere pressure (not including bulk resistor) ;
7. Insulated resistance: no less than 1,000M ohm in normal atmosphere pressure ;
8. Intensity of anti-current: DC 1,000V (AC,700V), no puncture and flash-over phenomenon in one minute ;
9. Retention strength: 7.7kg between jack and plug.
10. Label: clear label to ensure easy to management ;

telephone module		AS-KEY-T6	
SIGNATURE	SIGNATURE	DATE	DATE
DEVISER	NORMALIZER	DATE	DATE
PROOFREADER	RATIFIER	DATE	DATE
ASSESSOR	DATE	PAGE NUMBER OF ALL	PAGE HEADER
TECHNOLOGIST	DATE	SCALE	2:1
ANSHI Cixi Anshi communication Equipment Co., Ltd			

ENREGISTER OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER OF OLD BASE MAP

SERIAL NUMBER OF BASE MAP