



Key Specifications/Special Features

- 1.Operation temperature:-20 ℃ to 60℃, Relative humidity: 85%(30℃), Air pressure: 70-106Kpa.
- 2.With Cat5e keystone modules used for 19" cabinet ,Complete metalation and reed construction, modularization design ;
- 3.Contact pin: phosphor bronze and gold plating (20-50uinch), mating durability not less than 750 cycles ;
- 4.Anti-bum performance: plastic part made from PPO and PC or PBT , meeting the international standard ;
- 5.Intermediate resistance: no more than 20m ohm in normal atmosphere pressure (not including bulk resistor) ;
6. Insulated resistance: no less than 1,000M ohm in normal atmosphere pressure ;
- 7.The intensity of anti-currency: DC 1,000V (AC,700V), No puncture and flash-over phenomenon in one minute. Accord with industry standard ;
- 8.Backwave loss: $\geq 34\text{dB}(1 \leq f < 100\text{MHz})$
- 9.Minimum near end cross talk loss 100MHz: $\geq 43\text{dB}(100\text{MHz})$; Minimum far end cross talk loss 100MHz: $\geq 35.3\text{dB}(100\text{MHz})$
- 10.Label:clear label to ensure easy to manage ;
- 11.Type:unshielded
- 12.Standard: designed by international ISO/IEC11801 and TIA/EIA568 ;

				24 ports patch panel(pass-thru)				AS-PL-KA24ST	
SIGNATURE	QUANTITY OF LOCALITY	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	ANSHI Ctd Anshi communication Equipment Co.,Ltd
DEVISER		NORMALIZER						1:1.5	
PROOFREADER		RATIFIER							
ASSESSOR					PAGE NUMBER OF ALL	PAGE HEADER			
TECHNOLOGIST			DATE						

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE