



Key Specifications/Special Features

- 1.Operation temperature:-40℃ to 60℃, Relative humidity: 85%(30℃), Air pressure: 70-106Kpa.
- 2.With RJ45 keystone modules used for 19" cabinet ,Complete metalation and reed construction, modularization design ;
- 3.IDC: phosphor bronze and silver plating (20-50uinch), suitable diameter 0.4-0.6mm, durability 200 cycles ;
- 4.Contact pin: phosphor bronze and gold plating (20-50uinch), mating durability not less than 750 cycles ;
- 5.Anti-burn performance: plastic part made from PPO and PC or PBT or ABS, meeting the international standard ;
- 6.Intermediate resistance: no more than 2.5m ohm in normal atmosphere pressure (not including bulk resistor) ;
- 7.Insulated resistance: no less than 1,000M ohm in normal atmosphere pressure ;
- 8.The intensity of anti-currency: DC 1,000V (AC,700V), No puncture and flash-over phenomenon in one minute. Accord with industry standard ;
- 9.Label:clear label to ensure easy to manage ;

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE

				50 ports voice patch panel(6P4C)				AS-PL-V50	
SIGNATURE	IDENTITY OF QUALITY	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	
DEVISER			NORMALIZER					1:2	
PROOFREADER			RATIFIER						
ASSESSOR									
TECHNOLOGIST			DATE		PAGE NUMBER OF ALL	PAGE HEADER			
ANSHI Cixi Anshi communication Equipment Co.,Ltd									