



Key Specifications/Special Features

- 1.Environment condition: 5-40 degree Celsius , Relative humidity <85% (+30 degree Celsius), Atmospheric pressure: 70-106KPa ;
- 2.Pulling-out force: tin bronze and silver or tin plating (20-40uinch) ;
- 3.The performance of anti-burn: anti-burn PC , Combustibility achieved GB/T 5169.7-1985 standard ;
- 4.Specification: 4 pairs ;
- 5.Life: durability 200 cycles .

ENREGISTER
OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER
OF OLD BASE MAP

SERIAL NUMBER
OF BASE MAP

SIGNATURE

DATE

				110 clamp connection module(4 pairs)				XL-4025A	
SIGNATURE	DESIGNITY OF QUALITY	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	
DEVISER		NORMALIZER						2:1	
PROOFREADER		RATIFIER							
ASSESSOR									
TECHNOLOGIST		DATE			PAGE NUMBER OF ALL	PAGE HEADER			
								ANSHI Cixi Anshi communication Equipment Co.,Ltd	