



- 1、 The performance of anti-burn: PBT(UL94V-0) or anti-burn PC(UL94V-0), combustibility achieved GB/T 5169.7-1985 standard, Standing time after take off blue blaze <math>< 10s</math> (blaze of blue - 2、 Insulated resistance: no less than 1,0000M ohm in normal atmosphere pressure;
- 3、 The intensity of anti-currency: DC 1,000V (AC,700V) ; No puncture and flash-over phenomenon in one minute. Accord with industry standard ;
- 4、 IDC: phosphor bronze and silver plating (20-50uinch), suitable diameter 0.4-0.6mm, durability 200 cycles ;
- 5、 The performance of Intermediate : Insulation displacement connection(IDC), no corrosive area $\geq 50\%$ (after clamp);
- 6、 Pulling-out force: Insulation displacement connection(IDC),tin bronze and silver plating (20-40 u inch), pulling-out force not less than 25N ;
- 7、 Minimum near end cross talk loss :
- 8、 Attenuation:

Test item	Unit	Product standard		Remark
		f(MHz)	Min.	
Minimum near end cross talk loss	dB	1.0	65	
		4.0	65	
		10.0	60	
		16.0	56	
		20.0	54	
		31.25	50	
		62.5	44	
		100.0	40	

Test item	Unit	Product standard		Remark
		f(MHz)	Max.	
Attenuation	dB	1.0	0.1	
		4.0	0.1	
		10.0	0.1	
		16.0	0.2	
		20.0	0.2	
		31.25	0.2	
		62.5	0.3	
		100.0	0.4	

- 9、 Product standard:
YD/T926.3-1998 ' Telecommunication Generic Cabling System for Building Part 3: Connecting Hardware Requirements for Generic Cabling ' and designed by international ISO/IEC11801 and TIA/EIA568.

					25Pairs HF connection module				XL-4019	
SIGNATURE	DATE	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	ANSHI Cixi Anshi communication Equipment Co.,Ltd	
DEVISER		NORMALIZER						1:1		
PROOFREADER		RATIFIER								
ASSESSOR		DATE			PAGE NUMBER OF ALL	PAGE HEADER				
TECHNOLOGIST										

ENREGISTER OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER OF OLD BASE MAP

SERIAL NUMBER OF BASE MAP

SIGNATURE

DATE