



Key Specifications/Special Features

- 1、 Environment condition: -5-40 degree Celsius ; Relative humidity <85% (+30 degree Celsius); Atmospheric pressure: 70-106KPa ;
- 2、 Pulling-out force: phosphorus bronze and silver plating (20-40 uinch), pulling-out force not less than 25N ;
- 3、 The performance of anti-burn: PBT (UL94V-0) or anti-burn ABS (UL94V-0) , Combustibility achieved GB/T 5169.7-1985 standard ;
- 4、 Specification: 10 pairs
- 5、 Type: connection types
- 6、 Life: durability 200 cycles
- 7、 suitable diameter: 0.4-0.6mm(metal).

				10 Pairs clamp module (背插分离器)				XL-011H	
SIGNATURE	QUANTITY OF LOCALITY	DOCUMENT SERIAL NUMBER	SIGNATURE	DATE	DRAWING MARK SYMBOL	QUANTITY	WEIGHT	SCALE	ANSHI Ctd Anshi communication Equipment Co.,Ltd
DEVISER		NORMALIZER						2:1	
PROOFREADER		RATIFIER							
ASSESSOR		DATE			PAGE NUMBER OF ALL	PAGE HEADER			

ENREGISTER OF BORROW

TRACER

PROOFREADER

SERIAL NUMBER OF OLD BASE MAP

SERIAL NUMBER OF BASE MAP

SIGNATURE

DATE