



Key Specifications/Special Features

- 1.Operation temperature:-40 ℃ to 60 ℃, Relative humidity: 85%(30 ℃), Air pressure: 70-106kpa.
- 2.IDC: phosphor bronze and silver plating (20~50inch), suitable diameter 0.4-0.6mm, durability 200 cycles ;
- 3.Contact pin: phosphor bronze and gold plating (20~50inch), mating durability not less than 750 cycles ;
- 4.Anti-burn performance: plastic made from PPO and PC or PBT(UL94V-0), meeting the international standard ;
- 5.Intermediate resistance: no more than 20m ohm in normal atmosphere pressure (not including bulk resistor) ;
- 6.Insulated resistance: no less than 1,000M ohm in normal atmosphere pressure ;
- 7.Intensity of anti-current: DC 1,000V (AC,700V), no puncture and flash-over phenomenon in one minute ;
- 8.Label: clear label to ensure easy to management ;

ENREGISTER OF BORROW		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		ANSHI Cixi Anshi communication Equipment Co.,Ltd
TRACER		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		
PROOFREADER		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		ANSHI Cixi Anshi communication Equipment Co.,Ltd
SERIAL NUMBER OF OLD BASE MAP		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		
SERIAL NUMBER OF BASE MAP		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		ANSHI Cixi Anshi communication Equipment Co.,Ltd
SIGNATURE		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		
DATE		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		ANSHI Cixi Anshi communication Equipment Co.,Ltd
TECHNOLOGIST		SIGNATURE		DATE		DRAWING MARK SYMBOL		QUANTITY		WEIGHT		SCALE		

Cat5e keystone jack

XL-4012F